



Any Size! Any Color! No corrosion/rust!

Chem-Pruf®  
 P.O. Box 4560 Brownsville, TX 78523  
 Phone: 1-800-444-6924  
 Fax: 956/544-7943  
 E-mail: info@chem-pruf.com

**SARGENT**

**Passage 10U15LP**

**SARGENT**




**Cylindrical Passage**

**10U15 LP**

**15 Passage**



**LP Design**



**Specifications**

For Doors	1-3/4" (44mm) thick door adjustable to 2" (51mm) standard
Backsets	2-3/4" (70mm) standard 3-3/4" (95mm) backset available (23- prefix) 5" (127mm) backset available (25- prefix)
Cylindrical Housing	Steel zinc dichromate finish
Front	Wrought brass, bronze and stainless steel 2-1/4" (57mm) x 1-1/8" (29mm) Self-adjusting for flat to 1/8" (3mm) in 2" (51mm) bevel
Strike	800 curved lip strike standard Wrought brass, bronze and stainless steel 808 curved lip ANSI strike available (28- prefix) Wrought box strike available (WBS suffix)
Hand	Universal, not handed
Roses	Heavy wrought brass and bronze
Latchbolt	Brass 1/2" (13mm) throw 3/4" (19mm) throw for pairs of doors (41- prefix)
Cylinder	Brass, 6 pin, LA keyway standard
Keys	Two, nickel silver
Masterkeying	Can be masterkeyed or grand masterkeyed Construction key systems available
Finishes	3, 4, 9, 10, 10B, 10BL, 20D, 26, 26D
Prefixes	For detailed information see "Prefixes"
Door Prep	ANSI A115.2 (161) Modified
Minimum Stile	4-1/2" (114mm)

**Features and Benefits**

- Bi-directional lever operation—non handed
- Heavy duty lever spring
- Steel thru bolted mounting studs
- Three thru bolt position combinations
- Five year mechanical warranty

**Certification Compliance**

ANSI/BHMA	Meets ANSI A156.2 Series 4000 - Grade 1
UL	UL and UL listed to Canadian safety standards Listed for 3 Hour Doors (double doors require 41 - prefix)
Positive Pressure	Meets UL 10C and UBC 7-2 (1997)
USA	Complies with Buy America Act