



CHEM-PRUF P-SERIES FIXED WINDOW SYSTEMS

CORROSION RESISTANT

Chem-Pruf P-Series Fixed Windows are fabricated from heavy walled fiberglass pultrusion profiles and are available in both Non-UL Fire Rated and UL Fire-Rated designs. All of our fixed window systems are available in 3 standard and 24 optional pre-matched colors with custom color matching available.

NON-UL FIRE RATED

The non-UL fire rated constructions available include everything from simple 4-sided to multi-section window wall units. A choice of anchoring systems are available for bolt-in, built-in or bonded-in installations for various wall constructions.

UL FIRE RATED

The UL fire rated options outlined in the chart below have been successfully tested in accordance with UL 9 and UBC 7-4 for a 4-sided single window configuration.

All of our fixed window systems are available in 3 standard and 24 optional pre-matched colors with custom color matching available. Please contact Chem-Pruf with your specific fixed window product requirements.




Fire Rated Options

Hourly Fire Ratings: Up to 1-1/2 hours with UL approved ceramic glazing material. Up to 3/4 hours with UL approved wire glass glazing material.

Max Exposed Glass Area: 2340.5 sq. inches with UL approved ceramic glazing material
 Maximum width of exposed glass: 43"
 Maximum height of exposed glass: 54-3/4"
 1296 sq. inches with UL approved wire glass glazing material

Frame Profile Limitations: Face trims from 1" to 4" jamb depths to 13-1/2"

Frame Anchorage: Bolt-in or built-in masonry or poured concrete walls



SENNECA HOLDINGS

11502 CENTURY BOULEVARD, CINCINNATI, OH 45246

WWW.SENNECA.COM | QUOTES-ORDERS@SENNECA.COM | 800.543.4455

BROCHURE #: CPPFIXWIN-0520